

**3000 Series
15" CRT Touchmonitors**



SPECIFICATIONS

Model	1525C/1526C
Case/Bezel color	Beige/Dark gray
Display	Size: 15"; type: FST CRT
Image size, nominal	Default Horizontal: 10.2" (260 mm); vertical: 7.7" (195 mm)
Monitor dimensions	Width 14.3" (362 mm); height (including base) 12.9" (328 mm); depth (including base) 15.2" (385 mm)
Dimensional drawing number	MS500217 (available at elotouch.com)
Highest recommended resolution	800 x 600 at 85 Hz
Resolutions presets (VESA timing)	1024 x 768 at 60, 70, 75, or 85 Hz 800 x 600 at 60, 72, 75, or 85 Hz 640 x 480 at 60, 72, 75, or 85 Hz
Dot pitch, nominal	0.28 mm
Video bandwidth	67 MHz
Scanning frequency	Horizontal: 30–70 kHz; vertical 50–160 Hz
Input video format	Analog (no proprietary video card needed)
Input video signal connector	Mini D-Sub 15-Pin (female)
Power supply	90–264 VAC, 50–60 Hz
Power dissipation	70 W max.
Temperature	Operating 0°C to 40°C; storage –40°C to 60°C
Humidity	Operating 10% to 90%; storage 10% to 90%; noncondensing
Weight (approx.)	Net: 29 lb (13.0 kg); shipping 33 lb (15.0 kg)
Warranty	Monitor: 2 years
Agency approvals	UL, cUL, FCC, CE, CISPR22 Class B, TÜV-GS, MPR II (ITE per IEC/EN 60950)
On-screen display (OSD)	Digital OSD with lockout capability
Mounting options	Rigid (removable) base
Other features	VESA DDC 1/2 B Plug and Play

ORDERING INFORMATION

Color	Touch Technology	Touch Interface	Elo Part Number
Beige	iTouch	Dual serial/USB	396036-001
Dark gray	iTouch	Dual serial/USB	139862-001

- Users should independently evaluate the suitability of the product for their application.
- All prices, models, and availability subject to change without notice.

- Stock quantities may be limited. Larger quantities are available within one week.
- For Product Agency Certifications refer to our Web site.