



Desktop

1726C

3000 Series
17" CRT Touchmonitor

SPECIFICATIONS

Model	1726C	
Case/Bezel color	Dark gray	
Display type	FST CRT	
Display size	17" diagonal	
	Viewable	15.8" (406 mm)
Display area dimensions, nominal	Default	11.8" (300 mm) H x 8.9" (225 mm) V
Monitor dimensions	Width	15.9" (404 mm)
	Height (including base)	14.2" (360 mm)
	Depth (including base)	16.8" (426 mm)
Dimensional drawing number	MS500218(available at www.elotouch.com)	
Highest recommended resolution	1024 x 768 at 85 Hz	
Resolution presets	640 x 480 at 60, 72, 75, or 85 Hz; 800 x 600 at 60, 72, 75, or 85 Hz; 1024 x 768 at 60, 70, 75, or 85 Hz; 1152 x 864 at 75 Hz; 1280 x 1024 at 60 Hz	
Dot pitch, nominal	0.28 mm	
Video bandwidth	67 MHz	
Scanning frequency	Horizontal 30–70 kHz; vertical 50–160 Hz	
Input video format/connector	Analog (no proprietary video card needed)	
Input power connector	Mini D-Sub 15-Pin (female)	
Power supply	90–264 VAC, 50–60 Hz	
Power dissipation	75 W max.	
Temperature	Operating 0°C to 40°C; storage –40°C to 60°C	
Humidity	Operating 10% to 90%; storage 10% to 90%; noncondensing	
Weight (approx.)	Actual 32 lb (14.5 kg); shipping 37 lb (17.0 kg)	
Warranty	Monitor	2 years
	Touch technology	2 years iTouch; 5 years AccuTouch touchscreen
Other features	Digital on-screen display (OSD); removable base; sealing; VESA DDC 1/2 B Plug and Play; FCC/CE/ CISPR22 Class B; UL/CE/IEC 60950	

ORDERING INFORMATION

Touch Technology	Touch Interface	Surface Treatment	Elo Part Number	Agency Approvals
iTouch	Serial	Antiglare	D95678-000	UL, cUL, FCC, CE, TÜV-GS, MPR II
iTouch	USB	Antiglare	D90404-000	UL, cUL, FCC, CE, TÜV-GS, MPR II
AccuTouch	Serial	Antiglare	C25599-000	UL, cUL, FCC, CE, TÜV-GS, MPR II
AccuTouch	USB	Antiglare	816802-000	UL, cUL, FCC, CE, TÜV-GS, MPR II

- Beige available upon request
- Users should independently evaluate the suitability of the product for their application.
- All prices, models, and availability subject to change without notice.

- Stock quantities may be limited. Larger quantities are available within one week.
- For Product Agency Certifications refer to our Web site.