

LS3478-ER Scanner

Rugged cordless scanner

DATA SHEET

Capture bar codes over a wide range of distances

With the rugged cordless LS3478-ER scanner, you get the greatest working range of any available rugged scanner. You'll speed processes by allowing your employees to scan items on pallets as close as 4 inches (10 centimeters) away and shelves as far away as 45 feet (13.7 meters). In addition, your employees will be able to quickly switch from reading bar codes on inventory to capturing smaller symbologies on bar code menus and pick lists.

In the yard, warehouse, distribution center, manufacturing plant or retail store, these cordless handheld devices offer superior performance and reliability as well as a user-friendly form factor to help your employees comfortably operate the scanner even over eight-hour shifts. Multiple on-board interfaces ensure you'll be able to use the data capture devices with existing hosts, while giving you the flexibility to upgrade your systems without having to buy new scanners. You'll lay the foundation for an advanced data capture solution that grows with you as your business needs evolve.

Eliminate the cord, not performance

Your warehouse, manufacturing and even retail employees operate more efficiently when you eliminate the cable between the device and the host. Your forklift operator is able to drive to an aisle, scan a pallet up to 45 feet away and capture the data, without being cabled to the host. You save time and keep supply chain inventory up to date at all times. And, you've probably noticed the cable is a common point of failure in handheld devices operating in industrial facilities. Having no cord translates into less downtime from cable breakdowns.

Minimize equipment downtime

As innovative as it is rugged, the LS3478-ER delivers ergonomic and operational features for scan-intensive industrial applications under the harshest operating conditions. During industry tumble tests, it continued to provide reliable performance when subjected to multiple 6.5-foot (2-meter) drops to concrete. An IP65-rated seal makes it impervious to dust and water, and its exit window is scratch-resistant and recessed for the highest level of durability. As a result, you avoid unnecessary equipment downtime or expensive equipment replacement costs.

Provide versatility for your industrial applications

When you require quick scanner access and convenient out-of-the-way storage, such as on a forklift within a warehouse, the LS3478-ER features a built-in metal hook for attachment to a pulley. Workers will be able to access the scanner easily and stow it quickly when they're finished.



FEATURES

BENEFITS

Flexible working range: 4 in. (10 cm) to 45 ft. (13.7 m)

Allows workers to scan items at varying distances without having to move, reducing fatigue and speeding task completion

Cordless scanning

Enables real-time bar code data collection unrestricted by a cable, reducing repairs made necessary by cable failure

Rugged design withstands multiple 6.5-ft. (2-m) drops to concrete; 2,500 3.5-ft. (1-m) tumbles (5,000 hits)

Ensures maximum reliability with less downtime resulting from accidental drops

IP65-rated seal (electronic enclosure)

Protects against water and dust to ensure reliable performance in harsh industrial conditions, reducing unplanned downtime because of equipment failure

Bright LED and beeper with adjustable volume

Ensure positive user feedback in noisy environments with multiple modes of confirmation, so employees don't waste time trying to determine if a scan has been completed

Multi-point communication

Four scanners communicate to a single cradle for increased productivity

Bright 650 nm laser aiming dot

Delivers clearly visible line for more accurate scanning

Advanced data formatting

Eliminates costly modifications to the host software

Universal cable set

Allows for easy replacement and upgrades

Multiple on-board interfaces

Ensures flexible connectivity with different hosts, enabling you to maximize use of your existing technology

Working around noisy machinery or in poorly lit areas, your operators aren't always able to see or hear scanner feedback to quickly determine if the scans have completed. Bright LEDs and an adjustable-volume beeper on the LS3478-ER ensure that decode feedback is clearly visible and audible to users, saving valuable worker time.

End maintenance worries with a full suite of services and support


Even the most rugged scanners need a support plan to cover maintenance. That's why Symbol covers every aspect of your mobility solution— from network design to ongoing operations— providing unsurpassed breadth and depth of coverage to ensure all of your services and support needs are met.

Symbol Services offer:

- Professional planning, assessment and implementation services, forming the foundation of a successful solution
- A global team with unrivaled industry and product expertise, focused on Symbol product support
- Responsive customer support and maintenance services, ensuring your system operates seamlessly and efficiently

For more information on the cordless rugged LS3478-ER handheld scanner and the full line of accessories, contact us at +1.800.722.6234 or +1.631.738.2400, or visit us at www.symbol.com/ls3478er

¹ Roll (Tilt): Controlled by rotating the wrist clockwise or counterclockwise
² Pitch: Controlled by dropping or raising the wrist
³ Skew (Yaw): Controlled by rotating the wrist from left to right or vice versa



LS3478-ER specification highlights

Physical characteristics

Dimensions	7.34 in. L x 4.82 in. W x 2.93 in. D (18.65 cm H x 12.25 cm W x 7.43 cm D)
Weight (including LiON battery)	14.8 oz. (420 gm)
Battery	2200 mAh Lithium Ion Battery
Battery charge time	Fully charged (100%) in 3 hours
Color	Twilight Black and Yellow

Performance characteristics

Scanner type	Retrocollective
Light source	650 nm visible laser diode
Scan repetition	36 scans per second typical
Minimum element width	7.5 mil (0.191 mm)
Nominal working distance	See decode zone
Print contrast	25% minimum reflective difference
Roll (Tilt) ¹	+/- 10 degrees from normal
Pitch ²	+/- 65 degrees from normal
Skew (Yaw) ³	+/- 60 degrees from normal
Decode capability:	UPC/EAN, UPC/EAN with Supplemental, UCC/EAN 128, JAN 8 & 13, Code 39, Code 39 Full ASCII, Code 39 Trioptic, Code 128, Code 128 Full ASCII, Codabar (NW7), Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, Code 32, Bookland EAN, IATA, UCC/EAN RSS and RSS variants
Interfaces supported	RS232, Keyboard Wedge, Wand Emulation, Scanner Emulation, IBM 468X/469X, USB and Synapse

User environment

Operating temperature	-4° to 122° F (-20° to 50° C)
Storage temperature	-40° to 140° F (-40° to 60° C)
Humidity	5% to 95% relative humidity, noncondensing
Sealing	Sealed to IP65 specifications
Drop specifications	Unit functions normally after repeated 6.5-ft. (2-m) drops to concrete
Ambient light immunity	Immune to direct exposure of normal office and factory lighting conditions, as well as direct exposure to sunlight. Indoor: 450 foot candles/4,842 LUX Outdoor: 4,000 foot candles/43,040 LUX
Electrostatic discharge	Conforms to 15 kV air discharge and 8 kV of contact discharge

Cradles	STB 3408 and FLB 3408	STB 3478 and FLB 3478
Power requirements	4.75 – 14 VDC	4.75 – 14 VDC
Typical current draw		
Not charging	10 mA	105 mA @5V 45 mA @9V
Fast rate charge	915 mA @5V 660 mA @9V	915 mA @5V 660 mA @9V
Slow rate charge	480 mA @5V 345 mA @9V	480 mA @5V 345 mA @9V
Radio link	N/A	Bluetooth class 1 (2.4 GHz), Class 2

Radio specification

Radio range	100 meters direct line of sight. Adaptive frequency hopping allows co-existence with 802.11
Frequency	2.4 GHz

Regulatory

Input transient protection	IEC 1000-4-(2,3,4,5,6,11)
EMI/RFI	FCC Part 15 Class B, ICES-003 Class B, European Union EMC Directive, Japan VCCI/MITI/Dentori
Laser safety	IEC825-1 Class 2

Warranty

The LS3478-ER is warranted against defects in workmanship and materials for a period of 3 years (36 months) from date of shipment, provided that the product remains unmodified and is operated under normal and proper conditions. See full warranty for details.

Decode zone

LS3478-ER decode zone

About Symbol Technologies

Symbol Technologies, Inc., The Enterprise Mobility Company™, is a recognized worldwide leader in enterprise mobility, delivering products and solutions that capture, move and manage information in real time to and from the point of business activity. Symbol enterprise mobility solutions integrate advanced data capture products, radio frequency identification technology, mobile computing platforms, wireless infrastructure, mobility software and world-class services programs under the Symbol Enterprise Mobility Services brand. Symbol enterprise mobility products and solutions are proven to increase workforce productivity, reduce operating costs, drive operational efficiencies and realize competitive advantages for the world's leading companies. More information is available at www.symbol.com



Corporate Headquarters
Symbol Technologies, Inc.
 One Symbol Plaza
 Holtsville, NY 11742-1300
 TEL: +1.800.722.6234/+1.631.738.2400
 FAX: +1.631.738.5990

For Asia Pacific Area
Symbol Technologies Asia, Inc.
 (Singapore Branch)
 Asia Pacific Division
 230 Victoria Street #05-07/09
 Bugis Junction Office Tower
 Singapore 188024
 TEL: +65.6796.9600
 FAX: +65.6337.6488

For Europe, Middle East and Africa
Symbol Technologies
 EMEA Division
 Symbol Place, Winnersh Triangle
 Berkshire, England RG41 5TP
 TEL: +44.118.9457000
 FAX: +44.118.9457500

For North America, Latin America and Canada
Symbol Technologies
 The Americas
 One Symbol Plaza
 Holtsville, NY 11742-1300
 TEL: +1.800.722.6234/+1.631.738.2400
 FAX: +1.631.738.5990

Symbol Web site

For a complete list of Symbol subsidiaries and business partners worldwide, contact us at:
www.symbol.com
 Or contact our pre-sales team at:
www.symbol.com/sales



Specifications are subject to change without notice. Symbol® is a registered trademark, and The Enterprise Mobility Company is a trademark of Symbol Technologies, Inc. All other trademarks and service marks are proprietary to their respective owners.

For system, product or services availability and specific information within your country, please contact your local Symbol Technologies office or Business Partner.

Part No. LS3478ER Printed in USA 5/05 © 2005 Symbol Technologies, Inc. Symbol is an ISO 9001 and ISO 9002 UKAS, RVC and RAB Registered company, as scope definitions apply.