

# VS800

Compact Bar Code Scanner



#### **Ideal For:**

- Convenience Stores and Small Grocers
- Specialty Retailers and Pharmacies
- Area Registers in Discount Stores and Supermarkets

#### **Additional Features:**

- Standard POS interfaces; connectivity to most systems
- EAS deactivation option; one-step scanning and EAS deactivation
- Multiple mounting options; positions scanner out of the way
- Programmable two-step sleep mode and instant wake up; prolongs scanner life

#### **A winning combination for any business.**

#### **Maximum performance in minimal space.**

The VS800 compact scanner was designed specifically for point-of-sale applications, where space is always at a premium and where scanner performance is a critical component of efficiency and success.

The VS800 is the scanner to choose when you need reliable, full-functioned bar code scanning without sacrificing counter space. With optional mounts, operators can position the scanner at various angles to create a work environment that is highly convenient, comfortable, and productive.

#### **A Lot Of Technology In Very Little Space**

Using an advanced visible laser diode scanning system, the VS800 offers a large 8" / 20 cm depth-of-field and wide scan area for high-performance, hands-free scanning. With PSC's patented Edge™ software and enhanced decoding capabilities, the VS800 is fast and delivers very high first pass read rates on a variety of bar codes including labels that are long, truncated, partially obscured, or otherwise difficult to read. And it reads codes as small as 5 mils. All this means faster checkout for retail customers.

This versatile scanner autodiscriminates UPC or EAN plus 5 industrial symbologies. And the single, dual, or triple interfaces and extensive programming options deliver the flexibility needed to quickly and easily integrate the VS800 into your POS system.

#### **Advanced Design. Simple Operation. Built For Long Life and Fast ROI.**

Items are simply presented or swept by the VS800. The aggressive, omni-directional scan pattern virtually eliminates the need for operator training and minimizes the need to adjust or orient individual items.

The specially designed case of the VS800 is built to survive drops from a counter top and keep right on scanning. And it resists chipping, stains, and fading on its surface as well. With the VS800, maintenance is virtually nonexistent. Simply clean the scanner and window periodically and enjoy its productivity year after year.

There's no need to make compromises between quality and affordability. The VS800 delivers it all, high-end performance, compact design, and enhanced reliability at a price you can afford.



# Specifications

## VS800

### Mechanical

**Dimensions:** 5.9 x 3.4 x 3.0" / 15.0 x 8.6 x 7.6 cm  
**Weight:** 12.8 oz. / 363 g  
**Cable length:** 8 or 12' / 2.4 or 3.5 m extended

### Electrical

**Operating voltage:** 4.7 V to 14 VDC;  
 Universal Wedge Version – 5.2 V to 14 VDC  
**Power consumption:** 3 Watts maximum

### Decoding Capability

UPC A, E / EAN 8,13 / JAN 8, 13  
 • Edge™ stitching for UPC A, EAN 13 & Jan Add-ons  
 • UPC P2, UPC P5, Code 128  
**Industrial Codes**  
 • Code 128  
 • Code 93  
 • Code 39 (variable length; fixed length label stitching)  
 • Interleaved 2 of 5  
 • Codabar  
 • MSI / Plessey

2 label read

Autodiscriminate UPC Edge with Add-ons & 5 industrials

RSS 14 omni-stacked and expanded - optional

**NOTE:** With RSS enabled, Autodiscrimination is limited as follows:  
 • RSS with UPC/EAN/JAN or  
 • RSS with all industrial codes

### Optical

**Light source:** 650nm Visible Laser Diode (VLD)  
**Scan system:** Rotating polygon  
**Scan pattern:**  
 • Omnidirectional mode: 20 lines  
 • Scan speed: 1,500 lines per second (lps)  
 • Scan angles: 5

#### Motor:

- Speed: 4,500 rpm
- Speed to read (from motor off): <500 ms

**Depth-of-field:** Refer to chart on this page

**Resolution (minimum):** 5 mils / 0.13 mm

**Print contrast ratio:** 50% minimum

#### Label orientation:

- Pitch & Skew: ±80°
- Roll: 0° to 360°

#### Ambient Light tolerance:

200 foot candles / 2100 lux maximum

### Environmental

#### Temperature rating:

- Operating: 32° to 104° F / 0° to 40° C
- Storage: -40° to 158° F / -40° to 70° C

**Humidity:** 5 to 95% NC

**Shock (at 23° C):** withstands multiple 3-ft. / 1 m drops

**Water & Dust:** Resistant, IEC529 rating IP53

### Communications

#### Single interfaces:

- IBM USB Embedded
- Universal KBW w/USB keyboard

#### Dual interfaces:

- KBW / RS232

#### Triple interface:

- RS232 / KBW / IBM

### Safety & Regulatory

**Electrical:** Gost R; TÜV; UL; cUL

**Emissions:** Complies to FCC-A; BCIQ CNS 13438; EN 55022-B; AS/NZ 3458; VCCI-B

**Laser classification:** CDRH Class IIa;

(CAUTION: Laser radiation - do not stare into beam);  
 IEC 60825 Class 1



### Other

#### EAS compatibility

Integrated EAS hardware will work with Counterpoint IV, V, VI, and VII models available from Checkpoint Systems.



### Available Mount Options



P/N: 7-0448  
Universal Fixed



P/N: 7-0449  
Universal Fixed (tilt & swivel)



P/N: 7-0482  
Gooseneck Flexible



P/N: 7-0611  
Gooseneck Flexible (flat)

### Depth-of-Field Chart

(printing resolution, contrast and ambient light dependent)

Label Density	Range
5 mil	3.0" to 5.0" / 8.0 to 13.0 cm
7.5 mil	2.5" to 9.0" / 6.0 to 23.0 cm
10 mil	2.5" to 13.0" / 6.0 to 33.0 cm
13 mil	2.5" to 19.0" / 6.0 to 48.0 cm

### PSC Inc.

959 Terry Street  
 Eugene OR 97402-9150 USA  
 Tel: 800 695 5700 or 541 683 5700  
 Fax: 541 345 7140

### Specifications are subject to change without notice.

Additional information concerning this product or other PSC products and services can be found at the PSC website: [www.pscnet.com](http://www.pscnet.com) or contact your PSC representative for more information.



### PSC Worldwide Sales and Service locations

#### Australia - NSW

Tel: 61 2 9878 8999  
 Fax: 61 2 9878 8688

#### Belgium

Tel: 32 2 414 74 09  
 Fax: 32 2 410 11 63

#### Brazil

Tel: 55 11 5507 7721  
 Fax: 55 11 5507 7696

#### Chile

Tel: 562-339-7000  
 Fax: 562-339-7985

#### China

Tel: 86 10 6857 9048  
 Fax: 86 10 6857 8699

#### France

Tel: 33 1 64 86 71 00  
 Fax: 33 1 64 46 72 44

#### Germany

Tel: 49 6151 93580  
 Fax: 49 6151 935897

#### Hong Kong

Tel: 852 25846210  
 Fax: 852 25210291

#### India

Tel: 91 11 24621586  
 Fax: 91 11 24641662

#### Italy

Tel: 39 039 629031  
 Fax: 39 039 6859496

#### Japan

Tel: 81 3 3491 6761  
 Fax: 81 3 3491 6656

#### Latin America

Tel: 1 305 539 0111  
 Fax: 1 305 539 0206

#### Singapore

Tel: 65 6435 1311  
 Fax: 65 6226 1242

#### Spain

Tel: 34 91 746 28 60  
 Fax: 34 91 742 35 33

#### Sweden

Tel: 46 4010 84 92  
 Fax: 46 4010 84 91

#### United Kingdom

Tel: 44 1923 809500  
 Fax: 44 1923 809505